



# TYPE APPROVAL CERTIFICATE

Certificate no.:  
**TAE00003JF**  
Revision No:  
**2**

## This is to certify:

that the **Electrical Equipment**

with type designation(s)  
**SR3C..., SR3D..., SK3D...**

issued to

**H. Zander GmbH & Co. KG**  
**Aachen, Nordrhein-Westfalen, Germany**

is found to comply with

**DNV rules for classification – Ships, offshore units, and high speed and light craft**

## Application:

**Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV**

Issued at **Hamburg** on **2024-06-11**

for **DNV**

This Certificate is valid until **2029-06-10**.

DNV local unit: **Essen**

Approval Engineer: **Harald Amberger**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



## Product description

SR3C..., SR3D... Emergency Stop Safety Relays  
 SK3D... Safety Coupling Relays

Type:	SR3C..., SR3D...
Ratings:	
Operating voltage	AC 230 V, AC 115 V, AC/DC 24 V*, AC: 50-60 Hz
Safety contacts 3 NO	AC: 250 V, 2000 VA, 8 A for AC-12 250 V, 3 A for AC-15
	DC: SR3C: 40 V, 320 W, 8 A for DC-12 SR3D: 30 V, 240 W, 8 A for DC-12 24 V, 3 A for DC-13
Auxilliary contacts 1 NC	AC: 250 V, 500 VA, 2 A for AC-12 250 V, 3 A for AC-15
	DC: SR3C: 40 V, 80 W, 2 A for DC-12 SR3D: 30 V, 60 W, 2 A for DC-12

Type:	SK3D...
Ratings:	
Operating voltage	AC 230 V, AC 115 V, DC 24 V, AC: 50-60 Hz
Safety contacts 3 NO	AC: 250 V, 2000 VA, 8 A for AC-12 250 V, 5 A for AC-15
	DC: 30 V, 240 W, 8 A for DC-12 24 V, 4 A for DC-13
Auxilliary contacts 1 NC	AC: 250 V, 500 VA, 2 A for AC-12
	DC: 30 V, 60 W, 2 A for DC-12

Safety category 4, PL e acc. to EN ISO 13849-1 and SILCL 3 according to IEC 62061 / IEC 61508

Further ratings acc. manufacturer documentation.

## Application/Limitation

Location Classes:  
 Temperature: B, Humidity: B, Vibration: A

\* Insulating transformer acc. to EN60742 must be used.

Operating instruction of the manufacturer to be observed

## Type Approval documentation

Test report : 23.520.25/02-43-171/I dated 2003-12-08 (BG-PRÜFZERT) 08-12-2005 dated 2005-12-14 (RMS),  
 968/EZ344.00/09 dated 2009-02-13 (TÜV) IMST EMV-Prüfbericht Nr. Zander\_1247 dated 2014-01-23  
 TÜV Rheinland Bericht-Nr.: 968/M 221.01/14 dated 2014-01-31  
 Compare\_Techn. Data SR6 vs. OA5622 vs. HFA6A dated 2022-09-09  
 Änderungs- und Einflussanalyse\_Alternativ Relais dated 2022-09-09

## Tests carried out

IEC60204-1:2016, Cold, dry heat, damp heat, vibration.

## Marking of product

H. Zander - Type designation - Main data.

## **Periodical assessment**

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE